

DFCV-AD Q/S 9124

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

General notes

- 1. Adiabatic cooler capacities are tested according to EN 1048 for dry coolers.
- 2. TrilliumSeries Coolers of models with D6xx coil configuration have inlet and outlet connections at opposite ends.
- 3. Adiabatic pre-cooling sections are shipped separately and need to be installed on site.

Last update: 23/04/2024

DFCV-AD Q/S 9124



1. Fluid inlet connection; 2. Fluid outlet connection; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection.



Model	Nr. of Fans	Weights (kg)			Dimensions (mm)			Air Flow	Tube Internal	Surface	Connecti
		Oper. Weight (kg)	Ship. Weight(kg	Heaviest Section (kg)	L	W	Н	(m³/s)	Volume (dm³)	(m²)	ons
DFCV	8	3450	3110	2700	5181	2730	2810	22.4	364.0	2976.0	4
Q9124-											
D613-D-											
AD											
DFCV	8	3450	3110	2700	5181	2730	2810	22.4	364.0	2976.0	4
Q9124-											
L613-D-											
AD											
DFCV	8	2450	3110	2700	5181	2730	2810	22.4	364.0	2976.0	4
Q9124-											
M613-											
D-AD											
DFCV	8	3450	3110	2700	5181	2730	2810	22.4	364.0	2976.0	4
Q9124-											
S613-D-											
AD											
DFCV	8	3287	2786	2571	5181	2730	2810	42.4	364.0	2976.0	4
S9124-											
D613-D-											
AD											
DFCV	8	3730	3015	2800	5181	2730	2810	44.0	576.0	2668.0	4
S9124-											
D616-D-											
AD											
DFCV	8	3287	2786	2571	5181	2730	2810	42.4	364.0	2976.0	4
S9124-											
L613-D-											
AD											
DFCV	8	3730	3015	2800	5181	2730	2810	44.0	576.0	2668.0	4
S9124-											
L616-D-											
AD											
DFCV	8	3287	2786	2571	5181	2730	2810	42.4	364.0	2976.0	4
S9124-											
M613-											
D-AD											
DFCV	8	3730	3015	2800	5181	2730	2810	44.0	576.0	2668.0	4
S9124-											
M616-											
D-AD											
DFCV	8	3287	2786	2571	5181	2730	2810	42.4	364.0	2976.0	4
S9124-											
S613-D-											
AD											
DFCV	8	3730	3015	2800	5181	2730	2810	44.0	576.0	2668.0	4
S9124-											
S616-D-											
AD											